


	DESIG	N PH	DRAWN BY	DART	AEROSPACE PORT HADLOCK, V	
Γ	CHECKED APPROVED		DRAWING NO.	, , .	REV. A	
ı		#	- H	D6016		SHEET 1 OF 1
ſ	DATE		TITLE		SCALE	
	06.05.16		SKIDTUBE EXTENSION		1:1	
	Α		06.05.16	NEW ISSU	E	

## SPECIFICATION CONTROL DRAWING



## <u>NOTES</u>

1) D6016-XXX TUBE LENGTH

WHERE XXX IS LENGTH IN INCHES EG. 65" LONG TUBE: D6016-065

2) MATERIAL: 3.500" OD x 0.375" WALL 6061-T6/T6511 (WW-T-700/6 OR QQ-A-225/8 OR QQ-A-200/8) SEAMLESS ALUMINUM TUBE.

MINIMUM ULTIMATE TENSILE STRENGTH = 38 ksi MINIMUM YIELD TENSILE STRENGTH = 35 ksi

3) TOLERANCES ARE PER ASTM B210 AS FOLLOWS:

O.D.:  $\pm$  0.008 MEAN ( $\pm$ 0.016 INCLUDING OVALITY)

WALL: ±0.015 MEAN (±0.038 INCLUDING ECCENTRICITY)

LENGTH: XXX +0.188/-0.000

STRAIGHTNESS: 0.010" DEVIATION / 12" LENGTH

Copyright © 2006 by DART AEROSPACE USA, INC.

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.